



PONDSEAL

WATERPROOFING MEMBRANE FOR PONDS AND WATER FEATURES

Description

Pondseal is a polyurethane / acrylic co-polymer, water based coating which when fully cured, forms an impervious, flexible and aesthetically pleasing waterproofing membrane which enhances the look of the pond or water feature. It is non-toxic and formulated to be suitable for use with fish and plants. Being liquid applied, Pondseal conforms to any shape and provides seamless 'paint-on' pond liner in a variety of colours.

Uses

Duram Pondseal is used for the waterproofing of ponds, water features, bird baths, fountains and terracotta pots.

Suitable Surfaces

Duram Pondseal is suitable for use on the following sound, stable and properly primed surfaces:- Concrete, cement, cement rendered, brick work and block work, water resistant timber (particle board is excluded) and masonry surfaces.

Additional Uses

Pondseal can be used as a conventional waterproofing membrane but not in internal wet area applications such as shower recesses.

Specification

The information contained in this product data sheet is typical but does not constitute a full specification as conditions and specific requirements may vary from project to project. The instructions should be considered as a minimum requirement but the applicator or contractor must use their skill, knowledge and experience to carry out additional works as may be necessary to meet the requirements of the project. Specification for specific projects should be sought from the Company in writing.

Limitations

The structure must be dry to allow the product to properly cure. If the structure is subject to rising dampness, continual dampness or negative hydrostatic pressure then these problems must be solved prior to using Pondseal as the surface must be dry to enable the product to cure properly.

Benefits and Advantages

PONDSEAL is:

- a versatile membrane suitable for pond and water feature waterproofing applications.
- Suitable for use with fish and plants.
- is a urethane / acrylic co-polymer providing a strong, tough and flexible waterproofing membrane.
- Does not re-emulsify after proper curing.
- Quick curing.
- Easy to apply.
- Virtually odourless.
- UV resistant.
- Easily recoatable or repairable.

Precautions in Use

The product is considered safe if used correctly as intended and proper industrial hygiene and practices are used. Always observe safety precautions.

Priming and Surface Preparation

Good preparation is essential. Surfaces must be sound, stable, dry, clean and free of dust, loose, flaking, friable material and substances that may diminish adhesion.

Surface should be dry, sound, stable, free of gaps, dirt, dust, algae, fungus and other contaminants.

Construction

When constructing the water retaining structure, 2 ply plastic sheeting should be laid on the ground as a damp course prior to the laying of the concrete slab. If the structure is below ground the plastic sheeting should be turned up between the walls and the ground. This prevents rising damp and allows the structure to properly dry, which is essential.

The structure should be solid, stable, gap free and ideally have coved corners.

Priming

Prime all surfaces with Duram Primeseal applied at 3m² to 4m² per litre per coat so that the surface has a uniform, solid, off-white appearance. Excessively porous or friable surface should receive at least two priming coats.

Timber Surfaces must be primed with at least 2 coats of Duram Primeseal applied at 3m² to 4 m². per litre per coat. When in doubt apply a second coat of Duram Primeseal as this will enhance the waterproof quality of the system.

Allow primers to fully dry before applying Duram Pondseal.

Detailing Preparation

Joins, Gaps and Cracks

General

Joins, gaps and cracks should be suitably filled and sealed with an appropriate elastomeric sealant, preferably a polyurethane sealant, and allowed to cure.

Recommendation: The movement of small cracks should not be underestimated and should be at least covered with a flexible polyurethane sealant or additional coats of membrane.

After priming, as required, lay a strip of Duram Leak-Seal Tape over the join or crack pressing it firmly on to the substrate. The Duram membrane is then applied directly to the Duram Leak-Seal Tape and extending at least 75mm on to the adjacent surfaces.

If the Duram Leak-Seal is not used then a suitable bond breaker tape (such as duct tape) at least 48mm wide should be laid over the join or crack and apply a fully reinforced Duram membrane consisting of a base coat of membrane in to which the reinforcing fabric is embedded, a saturating coat of the Duram membrane ensuring that the fabric is entirely saturated and covered and then allowed to cure. At least one or two further coats are applied as per the Duram membrane's Product Data Sheet extending at least 75mm on to the adjacent surfaces.

If the Duram Leak-Seal is not used then follow the procedure as described under 'Large or Live Cracks'.

DURAM INDUSTRIES (PTY) LTD ACN 002 968 809 ABN 77 002 968 809
The Ultimate in Waterproofing & Protective Coating Technology

NEW SOUTH WALES: 51 Prince William Drive, Seven Hills, NSW 2147
QUEENSLAND: Unit 4, 29 Collinsvale Street, Rocklea QLD 4106
NEW ZEALAND: Consolidated Alloys (NZ) Ltd
55 Maurice Rd, Penrose, Auckland, New Zealand

Tel: (02) 9624 4077 Fax: (02) 9624 4079
Tel: (07) 3255 6478 Fax: (07) 3255 6258
Tel: 001164 9 622 9110 Fax: 001164 9 622 9119
Web: www.dlmwallace.co.nz

Detailing Preparation cont.

Corners

Prime as required.

Apply an adequate flexible polyurethane sealant, in accordance the manufacture's instruction and tool off to form a solid, coved or 45° fillet extending at least 10mm on to the adjacent surfaces. Apply the Duram membrane directly over the sealant and on the adjacent surfaces.

For Additional waterproofing protection the following additional steps should be taken: Lay a strip of Duram Leak-Seal Tape (self-stick, butyl mastic waterproofing membrane with a polyester backed reinforcing fabric) over the cured polyurethane sealant (as described above) pressing it firmly on the surface. Apply the Duram membrane directly over the tape and on the adjacent surfaces.

Outlets and Penetrations

The perimeter of waste outlets and around bases of penetrations should be sealed with a polyurethane sealant and allowed to dry.

Application

Stir well. Apply by brush or roller in coats of about 750 microns (0.75mm thick).

Apply in a minimum of two coats of Duram Pondseal. To perform correctly the dry film thickness of the membrane must be at least 1.2 mm.

Each coat must be fully cured before applying the next.

Reinforcing System

In areas such as corners and over joins and cracks the membrane should be used in conjunction with a reinforcing fabric (Duram Durascrim or fibreglass matting) the application consists of applying a base coat in to which the reinforcing fabric is laid followed by the application of a saturating coat ensuring that the product is worked well in to the fabric and that no wrinkles or bubbles are present and that fabric is entirely saturated and covered with product. Allow to cure. Apply one or two further coats of products.

It is essential that the system should be fully cured before filling with water. Although the membrane will readily cure, it is recommended that the water feature should not be filled within 7 days in good drying conditions. Prematurely filling can cause bubbling, blistering or re-emulsification of the membrane. The membrane will not be waterproof until it has fully cured.

Introducing Fish

Before introducing fish or plants, hose down the surfaces, rinse then fill and treat or age the water as per good practice,

Coverage

The stated average coverage rate may vary depending upon type, condition, porosity, texture of the surface and application technique.

Unreinforced: Minimum for two coats combined is 1.5 litres to 1.75 litres per m².

Reinforced: Minimum for two coats is 2.0 litres per m².

Colours

Pondseal is available in Midnight blue, Black and Sandstone. Dark colours are most popular as they show off the fish, plants and features better than light colours. Special colours are available upon request but minimum quantities will apply. Available in 1, 4 and 15 litres pails.

Drying and Curing

Drying and curing of the product is affected by type, dryness and porosity of the surface, temperature, humidity, ventilation, climate conditions and application technique and therefore drying and curing can only be given as a guide.

Pondseal is a fast drying water based product.

Expected curing at 25°C at 50% RH: Touch dry 4 hours per coat. Recoat 12 to 24 hours. Full cure within 48 but recommended filling after 7 days.

Protect from rain and inclement weather until fully cured. If product is damaged by rain prior to curing, drain water, remove uncured or damaged coating, allow to dry, clean (see preparation), ideally re-prime then re-coat as described in application. Cold, damp and high humid conditions will prolong curing.

Storage

Store in cool, dry area. Product is not flammable. Do not allow to freeze. Shelf life is 6 - 12 months in unopened containers.

Clean Up

Wet spills can be cleaned with water, but spills should be avoided as difficult to remove from porous surfaces.

Tiling, Topping or Top Coating

Usually not tiled or topped but, Pondseal is compatible with most tile adhesives and 3:1 sand : cement beds. Ideally the beds should be sealed / waterproofed to prevent the bed absorbing and holding water. Selection of the tile adhesive should be compatible with the flexibility of the substrate and suitable for immersion in water. Two pack adhesives systems are preferred. Tiling must be done in accordance with AS3958.1-1991 and adequate expansion joints installed.

Safety & Precautions

Pondseal is user friendly and safe to use if used correctly as intended. Nevertheless, protect eyes and skin and observe the safety precautions on the can and data sheet. The use of splash goggles and rubber gloves is recommended.

For full safety data refer to the products Material Safety Data Sheet. Observe precautions as per label.

CONDITIONS OF USE AND DISCLAIMER

The information contained in this data sheet is given in good faith based upon our knowledge and current information and does not imply warranty. The information is provided and the product sold on the basis that the product is used for its intended use and applied in a proper workman like manner in accordance with the instruction in this data sheet onto suitable and correctly prepared surfaces which shall remain sound, stable, free of structural defects, cracking, spalling concrete cancer, negative pressure, movement or other conditions that may effect the performance of the product. Deviations from application instructions may diminish or negate the performance of the product. Under no circumstances will the Company be liable for any loss, consequential or otherwise, arising from the use of the product. Liability is limited to the replacement of proven faulty product.